

# Model T Foamer

## Decontamination Foam Cleaning System

The **Model T Foamer** cleaning system is a rugged, portable, 45-gallon foam-generating unit designed to operate with compressed air supply with the following features:

- Simple construction provides minimal unit maintenance.
- Internal pressure-loaded closure prevents pressurized tanks from being opened.
- Portable size allows quick access to cleanup areas.
- Foam consistency can be adjusted.
- ASME-approved pressure tank and safety release valve.
- Constructed of corrosion-resistant polymers and stainless steel.

**Application:** The **Model T Foamer** is a portable foam applicator which provides a means of producing and applying CAPSUR®, METRAXT® and PENTAGONE® as a uniform foam onto horizontal, vertical, and overhead contaminated surfaces.

### Operating Requirements ( Customer )

1. Air Supply– 80 psi at 8 cfm.
2. Air Hose with 1/4" Industrial Interchange Nipple.

### Specifications

Maximum Tank Pressure 125 psi.  
 Tank Capacity 45 gallon  
 Empty Tank Weight 175 lbs.  
 ASME-Approved Tank and Pressure Relief Valve

The **Model T Foamer** is supplied with a foam hose which is 50 ft. long, 5/8" I.D., 200 psi-rated working pressure.



*The Model T Foamer is the ONLY foam applicator sold by Integrated Chemistries, Incorporated for use with CAPSUR®, PENTAGONE®, or METRAXT®. Selection and use of any other foamer is at the sole risk of the user.*

*For additional product information, contact:*

**INTEGRATED CHEMISTRIES, INC.**  
 P.O. Box 10558  
 White Bear Lake, Minnesota 55110

Phone (651) 426-3224  
 Fax (651) 426-3114  
 Email: [info@integratedchemistries.com](mailto:info@integratedchemistries.com)

